

UNCLASSIFIED

AD NUMBER

AD819939

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

**Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 08 SEP 1967.
Other requests shall be referred to Air Force Technical Applications Center, Washington, DC.**

AUTHORITY

AFTAC USAF ltr 28 Feb 1972

THIS PAGE IS UNCLASSIFIED

19
AD819939

FREQUENCY-WAVENUMBER ANALYSIS OF SIGNALS AND NOISE
RECORDED AT THE VERTICAL ARRAY AT APACHE, OKLAHOMA

8 September 1967

Prepared For

AIR FORCE TECHNICAL APPLICATIONS CENTER
Washington, D. C.

By

R. L. Sax
TELEDYNE, INC.

Under

Project VELA UNIFORM

Sponsored By

ADVANCED RESEARCH PROJECTS AGENCY
Nuclear Test Detection Office
ARPA Order No. 624

FREQUENCY-WAVENUMBER ANALYSIS OF SIGNALS AND NOISE
RECORDED AT THE VERTICAL ARRAY AT APACHE, OKLAHOMA

SEISMIC DATA LABORATORY REPORT NO. 196

AFTAC Project No.:	VELA T/6702
Project Title:	Seismic Data Laboratory
ARPA Order No.:	624
ARPA Program Code No.:	5810
Name of Contractor:	TELEDYNE, INC.
Contract No.:	F 33657-67-C-1313
Date of Contract:	2 March 1967
Amount of Contract:	\$ 1,736,617
Contract Expiration Date:	1 March 1968
Project Manager:	William C. Dean (703) 836-7644

P. O. Box 334, Alexandria, Virginia

AVAILABILITY

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

This research was supported by the Advanced Research Projects Agency, Nuclear Test Detection Office, under Project VELA-UNIFORM and accomplished under the technical direction of the Air Force Technical Applications Center under Contract F 33657-67-C-1313.

Neither the Advanced Research Projects Agency nor the Air Force Technical Applications Center will be responsible for information contained herein which may have been supplied by other organizations or contractors, and this document is subject to later revision as may be necessary.

TABLE OF CONTENTS

	Page No.
ABSTRACT	
ARRAY RESPONSE	1
AMBIENT NOISE	4
SIGNAL, NOISE PRECEDING SIGNAL, AND CODA	5
FIGURES	
1. Simulated Signal Using Acoustic Log Propagation Velocities Measured at APOK	
2. Simulated Noise	
3. Ambient Noise	
4. Noise Sample Before The Aleutian Earthquake	
5. Main Pulse of The Aleutian Earthquake	
6. Coda Following The Main Pulse of The Aleutian Earthquake	
7. Mirror Imaged Ambient Noise Sample	
8. Mirror Imaged Noise Before Aleutian Earthquake	
9. Mirror Imaged Main Pulse of Aleutian Earthquake	
10. Mirror Imaged Coda of Aleutian Earthquake	

ABSTRACT

The seismic data analyzed include an Aleutian earthquake, several samples of ambient noise along with the noise occurring before the event, and a 25 second sample of coda following the signal. The signal coda sampled had nearly uniform power. A preliminary interpretation of the noise and signals strongly suggests the importance of energy conversions possibly due to the complex geology at APOK. The geology is known to be very complex and is characterized to first order a thick wedge of low velocity strata imbedded in material of higher propagation velocity. The evidence of conversion is based on the asymmetry of the F-K spectrum of ambient noise with respect to positive and negative wave number. The results indicate a predominance of obliquely incident up-going waves at all frequencies. Further, the signals and coda similarly displayed anomalous down-going pulses attenuated by approximately 6 db with respect to the up-going pulse. Further, the down-going pulse contains lower frequencies than the up-going pulse and has a much lower apparent vertical velocity. The results obtained by mirror imaging the vertical array indicated that a loss of approximately 3 db would be encountered in using a conventional signal model at this site.

ARRAY RESPONSE

Due to the finite dimension of the array and the uneven spacing of sensors, and finite duration of the samples, the response to a sinusoidal wave input can be very complicated and can possibly lead to misinterpretations. For an analysis of the response of a continuous finite array consider the response to sine wave inputs.

$$p(t, x) = \begin{cases} \exp[i\omega_0(t-x/c)] + \exp[i\omega_0(t+x/c)] & \text{when } T_1 \leq t \leq T_2 \text{ and } X_1 \leq x \leq X_2 \\ 0 & \text{elsewhere} \end{cases}$$

$$F(\omega, k) = \int_{X_1}^{X_2} \int_{T_1}^{T_2} p(t, x) e^{-i\omega t} e^{-ikx} dt dx = S(\omega) Y(k)$$

$$S(\omega) = \frac{1}{i(\omega_0 - \omega)} [e^{i(\omega_0 - \omega)T_2} - e^{i(\omega_0 - \omega)T_1}]$$

$$P_T(\omega) = S(\omega) \overline{S(\omega)} = \frac{2 \cdot \{ 1 - \cos [(\omega_0 - \omega) (T_2 - T_1)] \}}{(\omega_0 - \omega)^2}$$

$$\text{Let } Y(k) = Y_1(\omega_0/c - k) + Y_2(\omega_0 + k)$$

$$Y_1(k) = \frac{1}{i(\omega_0/c - k)} [e^{i(\omega_0/c - k) X_2} - e^{i(\omega_0/c + k) X_2}]$$

$$Y_2(k) = \frac{1}{i(\omega_0/c + k)} [e^{i(\omega_0/c + k)x_2} - e^{i(\omega_0/c + k)x_1}]$$

$$P_X(k) = (Y_1 + Y_2)(\bar{Y}_1 + \bar{Y}_2) = Y_1\bar{Y}_1 + Y_2\bar{Y}_2 + (Y_1\bar{Y}_2 + Y_2\bar{Y}_1)$$

$$Y_1\bar{Y}_1 = \frac{2 \cdot \{1 - \cos [(\omega_0/c - k)(x_2 - x_1)]\}}{(\omega_0/c - k)^2}$$

$$Y_2\bar{Y}_2 = \frac{2 \cdot \{1 - \cos [(\omega_0/c + k)(x_2 - x_1)]\}}{(\omega_0/c + k)^2}$$

$$\begin{aligned} Y_1\bar{Y}_2 + Y_2\bar{Y}_1 &= \frac{2}{(\omega_0/c - k)(\omega_0/c + k)} \{ \cos 2kx_2 + \cos 2kx_1 \\ &\quad - \cos [(\omega_0/c - k)x_1 - (\omega_0/c + k)x_2] \\ &\quad - \cos [(\omega_0/c - k)x_2 - (\omega_0/c + k)x_1] \} \end{aligned}$$

The total power response of the array is

$$R(\omega) = P_T(\omega) P_X(k)$$

From this it is clear that the response of the F-K spectrum to a sinusoidal wave of given frequency and wave number is a complicated function of both frequency and wave number and in practice is even much more so due to finite and uneven sampling in space. Thus to make rigorous use of the F-K analysis

as a tool one should compare a model with the observed data, and conclude that the model is adequate only if the F-K spectra qualitatively match the model. In this preliminary report, this is not stressed enough, but as a cautionary aid the response of an impulse for the case of infinite apparent vertical phase velocity is shown with each F-K spectrum, and several synthetic cases are run for simple models of a signal and a model of the ambient noise.

The signal model is generated with 1.25 cps pulse with a .8 second echo at the source and with a receiver echo delayed by using appropriate uphole times obtained from propagation velocities observed at APOK and with a surface reflection coefficient of 0.9. The signal model F-K spectrum is shown on Figure 1. The split peak in the spectrum is due to the source echo which nulls at 1.25 cps. The strip at the bottom shows the array response.

The noise is simulated by taking random numbers from a Gaussian population and passing them through a tuned filter at .25 cps and 2.0 cps to obtain a model of the noise at the surface. The model of the noise at underlying depth is obtained from a stationary Markov chain; for example, the noise at the i^{th} level is taken as a fraction of the noise of the $(i - 1)^{\text{th}}$ channel added to a new random realization passed through the tuned filters. An example of this noise model is shown on Figure 2. It is similar to ambient noise observed at APOK (see Figure 3), except that the highly correlated noise peaks observed in the signal band ($.7 \leq f \leq 2.0$) were not put into the model. In the model the sharp spectral peak at .25 cps (Figure 2) is for highly correlated noise between channels contrasted with that at 2.0 cps where the noise which is uncorrelated between channels, with the results that the peak is spread broadly over all wave numbers.

AMBIENT NOISE

The ambient noise spectrum derived from a four minute sample is shown on Figure 3. Comparing this with noise generated from a Markovian process, the .25 and 2.0 cps peaks are of similar character suggesting very high correlation between channels for the .25 cps peak and very low correlation for the 2.0 cps noise peak. The principal difference between the observed noise at APOK on Figure 3 and the synthetic noise generated using the extremely simple linear state model is a rotation of the whole pattern toward negative wave numbers. This same effect can be produced by inputting the random function to a process which produces negative delays or lead time equal to X/C representing conversion to up-going waves where the apparent vertical phase velocity C is obtained from the slope of the line shown on Figure 3. The value obtained for C is approximately 12 km/sec corresponding to an incidence angle of about 75° . This suggests the possibility of Stonely waves guided upwards along the thick low-velocity layer, dipping 15° . This possibility is qualitatively consistent with the anomalous signal shown on Figure 5.

Other differences between observed noise on Figure 3 and the model on Figure 2 are the three noise peaks at 1.0 cps, 1.4 cps, and 1.6 cps. The 1.0 and 1.4 peaks appear to be highly correlated between channels; the 1.6 shows low correlation in the noise between adjacent channels. These peaks in the signal band appear to have nearly infinite vertical phase velocity and are probably due to Rayleigh waves, i.e., vertical and possibly also horizontal standing waves trapped in the basin bounded by higher velocity basement complex rocks.

SIGNAL, NOISE PRECEDING SIGNAL, AND CODA

A 30-second noise sample before the arrival of the Aleutian event is shown on Figure 4. Comparing this with the ambient noise samples on Figure 3 we note the same asymmetry in the F-K spectrum. In addition, up-going body waves are indicated by peaks at .85 cps, 1.25 cps, 1.5 cps and 2.0 cps. There is much weaker indication of down-going waves at .85 cps, down by 3 db from the up-going waves. Waves of infinite vertical phase velocity (possibly Rayleigh waves,) are indicated by the series of peaks occurring along the frequency axis at $k = 0$. For this sample, these peaks are indicated with approximately the same power as the up-going body waves.

A 6-second sample of the earthquake pulse is shown on Figure 5. The up-going pulse gives spectral peaks at .85 cps, 1.20 cps, and 1.9 cps. The apparent vertical phase velocity is approximately the same as that shown by Figure 4 for the noise preceding the signal. Lower than expected vertical phase velocities suggest departure from the simple model of a pulse and echo based on acoustic log velocities (Figure 1). The apparent velocities are lower by at least fifteen to twenty percent. Also, the down-going earthquake pulse is even more anomalous. The amplitude is down 6 db from that of the up-going pulse; the apparent vertical velocity is very low; and the .85 cps peak down-going phase appears to contain lower frequency. A possible explanation of the anomalous signal can be based on dipping beds.

This may help to explain the anomalous low amplitude down-going reflection. The anomalous apparent vertical velocities may result from forward scattered P-S conversions, especially at the surface, due to anomalously high angle of emergence. Looking again at Figure 5, there appears to be signal peaks at nearly infinite vertical phase velocity.

Although possibly due to the array response, no such effect is observed on the simulated signal on Figure 1 which, of course, uses the same array geometry.

A 30-second sample of the coda following the signal is shown on Figure 6. These show apparent spectral peaks in the signal at .8 cps, 1.1 cps, and 1.35 cps. The overall character of the coda F-K spectrum is more similar to the signal than the noise preceding the signal, but is yet considerably different in detail from that of the signal.

Figures 7, 8, 9, and 10 are processed by taking the mirror image of the vertical array, which aligns the up-going and down-going pulses into a single step-out pattern. This will attenuate conversions to up or down-going P or S waves and amplify normally reflected P pulses and Rayleigh waves. It will also effectively double the aperture of the array for these kinds of waves. Figure 7 for the ambient noise shows body waves down 3 to 6 db from those of apparently infinite vertical phase velocity. Similar results are shown for the noise before the Aleutian event on Figure 8, also showing the noise field to be down considerably lower in the signal event. However, due to the grossly anomalous nature of the signal at APOK, the signal and coda are also down by 6 db compared to 3 db for the noise preceding the signal. Thus a loss of at least 3 db is expected if the signal model at APOK is taken as a normal up-going pulse and echo. For the imaged array, the frequency of F-K spectral peaks appear to be more consistent between the signal and its coda. The imaging techniques appears to eliminate conversions other than a simple echo at the surface.

VFKSPTRM SIMULATED SIGNAL

DATA CHANNEL NO. = 1 NO. OF CHANNEL = 5
 SAMPLING RATE = 20.00 STARTING POINT = 300 TOTAL POINTS = 120
 THE NUMBER OF SHOOTING TIME = 6

CHANNEL ID	SCALE FACTOR	DEPTH	N H	SYMBOL
A1	1.00	.015	0 - 4	4
A2	1.00	1.660	6 - 9	6
A3	1.00	1.990	12 - 19	2
A4	1.00	2.290	16 - 21	8
A5	1.00	2.910	24 - 27	.




Figure 1. Simulated signal using acoustic log propagation velocities measured at APOR

VFKSPTM SIMULATED AMBIENT NOISE

SEISMOLHAM NO. = 1 NO. OF CHANNEL = 8
 SAMPLING RATE = 20.00 STARTING POINT = 1 TOTAL POINTS = 4000
 THE NUMBER OF SMOOTHING TIME = 5

CHANNEL ID	SCALE FACTOR	DEPTH	U	S	SYMBOL
A1	1.00	.020	0	-3	0
A2	1.00	1.000	0	-9	0
A3	1.00	1.070	12	-19	2
A4	1.00	2.270	10	-21	0
A5	1.00	2.000	24	-27	1




Figure 2. Simulated noise

VFKSPTRM AMBIENT NOISE STATION AF0K

SEISMIC NO. • 7843

NO. OF CHANNELS

SAMPLING DATA = 20.00 STARTING POINT = 1 TOTAL POINTS = 40.00

THE NUMBER OF APPROXIMATING LINES

	SYMBOL
0 = 3	0
0 = 0	0
12 = 15	0
10 = 21	0
24 = 87	0




Figure 3. Ambient noise

VFKSPTRM AMBIENT NOISE STATION APOK

RECORDER NO. = 8893 NO. OF CHANNEL = 5

SAMPLING RATE = 80.00 STARTING POINT = 1 TOTAL POINTS = 512

THE NUMBER OF SMOOTHING-TIME = 8

CHANNEL ID	SCALE FACTOR	DEPTH	0	SYMBOL
DW5	1.00	.015	0	0
DW4	1.00	.1600	0	0
DW3	1.00	.1600	00	0
DW2	1.00	.2900	00	0
DW1	1.00	.0610	00	0




Figure 4. Noise sample before the Aleutian Earthquake

VFKSPTRM EARTHQUAKE ALEUTIAN ISLAND, STATION APOK

BOTINOGHAM NO. = 6373 NO. OF CHANNEL = 9
 SAMPLING RATE = 20.00 STARTING POINT = 660 TOTAL POINTS = 128
 THB NUMBER OF SMOOTHING TIME = 8




Figure 5. Main pulse of the Aleutian Earthquake

VFKSPTRM ALEUTIAN EARTHQUAKE CODA

8616HGDRM NO. = 6353 NO. OF CHANNEL = 5
SAMPLING RATE = 20.00 . . . STARTING POINT = 600 TOTAL POINTS = 518

THE NUMBER OF SHOOTING-TIME - 2

CHANNEL ID	SCALE FACTOR	DEPTH	SYMBOL
DW5	1.00	615	•
DW4	1.00	1,660	•
DW3	1.00	1,690	•
DW2	1.00	2,290	•
DW1	1.00	2,616	•




Figure 6. Coda following the main pulse of the Aleutian Earthquake

VEKSITIM AMBIENT NOISE STATION APOK

SEISMICGRAM NO. = 7993

NO. OF CHANNEL = 10 (MIRROR IMAGED)

SAMPLING RATE = 20.00 STARTING POINT = 1 TOTAL POINTS = 4096

THE NUMBER OF SMOOTHING TIME = 5

CHANNEL 10	SCALE FACTOR	DEPTH	D B	SYMBOL
0.1	1.00	-2.888		
0.2	1.00	-2.270		
0.3	1.00	-1.970	0 - 3	0
0.4	1.00	-1.660	6 - 9	6
0.5	1.00	-0.028	12 - 15	2
0.6	1.00	.020	18 - 21	8
0.7	1.00	1.668	24 - 27	7
0.8	1.00	1.978		
0.9	1.00	2.270		
0.1	1.00	2.888		




Figure 7. Mirror imaged ambient noise sample

SFISHMUGAH NO. * 6393
 NO. OF CHANNEL * 10 (MIRROR IMAGED)
 SAMPLING RATE = 20.00 STARTING POINT = 1 TOTAL POINTS = 512
 THE NUMBER OF SMOOTHING TIME = 2

CHANNEL ID	SCALE FACTOR	DEPTH	D.B.	SYMBOL
DW1	1.00	-2.910	0 - 3	0
DW2	1.00	-2.398	6 - 9	0
DW3	1.00	-1.990	12 - 15	2
DW4	1.00	-1.688	18 - 21	0
DW5	1.00	-0.015	24 - 27	0
DW6	1.00	.015		
DW7	1.00	1.688		
DW8	1.00	1.990		
DW9	1.00	2.398		
DW10	1.00	2.910		




Figure 8. Mirror imaged noise before Aleutian Earthquake

VFKSPTRM ALEUTIAN EARTHQUAKE CODA, STATION APOK

SFISMOGHAN NO. = 6393

NO. OF CHANNEL = 10 (MIRROR IMAGED)

SAMPLING RATE = 20.00 STARTING POINT = 800 TOTAL POINTS = 912

THE NUMBER OF SMOOTHING TIME = 2

CHANNEL ID	SCALE FACTOR	DEPTH	D	S	SYMBOL
0W1	1.00	-2.910	0	3	0
0W2	1.00	-2.290	6	9	0
0W3	1.00	-1.990	12	15	2
0W4	1.00	-1.680	18	21	0
0W5	1.00	-0.015	24	27	0
0W6	1.00	.815			
0W7	1.00	1.680			
0W8	1.00	1.990			
0W2	1.00	2.290			
0W1	1.00	2.910			




Figure 9. Mirror imaged main pulse of Aleutian Earthquake

VFKBPTMR EARTHQUAKE ALEUTIAN ISLAND, STATION A/MOK

SFISHMNGH NO. = 6323

NO. OF CHANNEL = 10

(MIRROR IMAGED)

SAMPLING RATE = 20.00 STARTING POINT = 660 TOTAL POINTS = 128

THE NUMBER OF SMOOTHING TIME = 0

CHANNEL ID	SCALE FACTOR	DEPTH	U B	SYMBOL
DW1	1.00	-2.910	0 - 3	0
DW2	1.00	-2.290	6 - 9	6
DW3	1.00	-1.990	12 - 15	2
DW4	1.00	-1.680	18 - 21	8
DW5	1.00	-0.015	24 - 27	.
DW6	1.00	.015		
DW7	1.00	1.680		
DW8	1.00	1.990		
DW2	1.00	2.290		
DW1	1.00	2.910		




Figure 10. Mirror imaged coda of Aleutian Earthquake

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) TELEDYNE, INC. ALEXANDRIA, VIRGINIA		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP ----
3. REPORT TITLE FREQUENCY-WAVENUMBER ANALYSIS OF SIGNALS AND NOISE RECORDED AT THE VERTICAL ARRAY AT APACHE, OKLAHOMA		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Scientific		
5. AUTHOR(S) (Last name, first name, initial) Sax, Robert L.		
6. REPORT DATE September 8, 1967		7a. TOTAL NO. OF PAGES 17
8a. CONTRACT OR GRANT NO. F 33657-67-C-1313 b. PROJECT NO. VELA T/6702 c. ARPA Order No. 624 d. ARPA Program Code No. 5810		8b. ORIGINATOR'S REPORT NUMBER(S) 196
		9b. OTHER REPORT NU(S) (Any other numbers that may be assigned this report) --
10. AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.		
11. SUPPLEMENTARY NOTES ---		12. SPONSORING MILITARY ACTIVITY ADVANCED RESEARCH PROJECTS AGENCY NUCLEAR TEST DETECTION OFFICE WASHINGTON, D. C.
13. ABSTRACT <p>The seismic data analyzed include an Aleutian earthquake, several samples of ambient noise along with the noise occurring before the event, and a 25 second sample of coda following the signal. The signal coda sampled had nearly uniform power. A preliminary interpretation of the noise and signals strongly suggests the importance of energy conversions possibly due to the complex geology at APOK. The geology is known to be very complex and is characterized to first order a thick wedge of low velocity strata embedded in material of higher propagation velocity. The evidence of conversion is based on the asymmetry of the F-K spectrum of ambient noise with respect to positive and negative wave number. The results indicate a predominance of obliquely incident up-going waves at all frequencies. Further, the signals and coda similarly displayed anomalous down-going pulses attenuated by approximately 6 db with respect to the up-going pulse. Further, the down-going pulse contains lower frequencies than the up-going pulse and has a much lower apparent vertical velocity. The results obtained by mirror imaging the vertical array indicated that a loss of approximately 3 db would be encountered in using a conventional signal model at this site.</p>		

DD FORM 1 JAN 64 1473

Unclassified
Security Classification

Unclassified

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Seismology						
Seismic Noise						
Deep Well						
Spectrum						
Signal Analysis						
INSTRUCTIONS						
1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.	Imposed by security classification, using standard statements such as:					
2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Date" is included. Marking is to be in accordance with appropriate security regulations.	(1) "Qualified requesters may obtain copies of this report from DDC."					
2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.20 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.	(2) "Foreign announcement and dissemination of this report by DDC is not authorized."					
3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.	(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through .."					
4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is cover.	(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through .."					
5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.	(5) "All distribution of this report is controlled. Qualified DDC users shall request through .."					
6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.	If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.					
7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.	11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.					
7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.	12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.					
8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.	13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.					
8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.	It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).					
9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.	There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.					
9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).	14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.					
10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those						

Unclassified

Security Classification